



paint specification & estimated consumption

Owner : TAL
Size : 20' DV

Date : 15th Oct., 2010

<u>PRODUCT NAME</u>	<u>LOCATION</u>	<u>AREA(m²)</u>	<u>D.F.T.(u)</u>	<u>S.V.(%)</u>	<u>L.R.</u>	<u>S.R.(m²/L)</u>	<u>CON.(KG)</u>
Zinc rich epoxy primer M114-9000	S/P	156	10	49	0.10	44.10	7.78
Zinc rich epoxy primer M114-9000	External	65	20	49	0.20	19.60	7.30
Epoxy primer M131-3579	External	65	40	51	0.50	6.38	13.25
Acrylic topcoat M210-TAL Brick brown	External	65	40	42	0.50	5.25	14.86
		TOTAL:	110				
Zinc rich epoxy primer M114-9000	Internal	65	10	49	0.20	39.20	3.65
Epoxy topcoat M281-Ral7035	Internal	65	60	58	0.60	3.87	21.85
		TOTAL:	80				
Zinc rich epoxy primer M114-9000	Base	22	20	49	0.20	19.60	2.47
		TOTAL:	30				
Thinner 9010030 (150% For shoppriming)							11.67
Thinner 9010015 (25% For M114,M131,M281)							12.13
Thinner 9030001 (25% For M210)							3.71
						TOTAL:	98.68